


Plotter DK – C12



Product Features



Adopts high-precision steel axes ,can prevent slipping while cutting long materials



Ultra pressure, capable of punching thick engineering materials



10 silica gel buttons, easy-to-use and durable



4*8 high resolution LCD back light display , suitable for different work surroundings



High Speed Arithmetic Microprocessor,stable processing, low noise operation yet without zigzag while cutting



User-friendly Design , allows to adjust cutting force and working speed while



Delicate, high strength aluminium alloy body



USB interface to connection computer also support hot-plug



Support Windows 2000/Windows 32 bits/Windows 64 bits/Windows7/Mac system



Unique count function, data retention are performed even power cut-off



LED positioning, contour cut function (Optional)

Specifications

Model	C12
Acceptable Media Width	415mm
Max.Cutting Width	305mm/12Inch
Operating system	Windows 32 bits / Windows 64 bits* / Windows7* / Mac*
Interface	RS232C, USB
Control Panel	10Silica gel buttons
Driver	Digital DC, Step Motor, Micro-step Driver
Display	4*8 High Resolution LCD
Drawing Instruction	HP-GL, DMPL
Max. Cutting Speed	600mm/s
Max. Cutting Thickness	1mm
Pressure	50g~800g, 160 Ajustable
Mechanical Precision(mm)	0.025mm
Repeat Accuracy	< ±0.1mm
Power Supply	AC90~240V/50Hz~60Hz
Positioning Mode	Bounded System,Random Original Point Setting
Work Mode	Roller
Operating Environment	Temperature:+5°C-35°C,Relative Humidity:30%-70%
Support Mode	Desktop
Net Weight	585*265*270mm / 9kg
Gross Weight	715*380*395mm / 12.3kg